



نمایندگی اندرس هاوزر در ایران
مشاوره، تامین، خدمات پس از فروش
راه ارتباطی:

۰۹۱۲۲۵۶۵۷۴۳ – ۰۹۳۵۲۵۶۵۷۴۳

tkpcontrol.ir

info@tkpcontrol.ir



Technical Information Liquiphant FTL31

Vibronic

Point level switch for liquids

Application

The Liquiphant FTL31 is a point level switch for liquids and is used in tanks, vessels and pipes.

It is used for overflow protection or pump protection in cleaning and filter systems as well as in cooling and lubrication vessels, for instance.

Ideal for applications in which float switches or conductive, capacitance and optical sensors have been used up to now. The Liquiphant FTL31 also works in areas where these measuring principles are not suitable due to conductivity, buildup, turbulence, flow conditions or air bubbles.

The Liquiphant FTL31 can be used for process temperatures up to:

- 100 °C (212 °F)
- 150 °C (302 °F)

Not suitable for hazardous areas.

The use of the Liquiphant FTL33 is recommended for hygiene areas.

Your benefits

- Operational safety, reliability and universal application thanks to the tuning fork measuring principle
- Robust stainless steel housing (316L), optionally available with M12x1 plug with IP69 protection
- External function test with test magnet
- Onsite function check possible thanks to LED indication
- Compact design for easy installation even in confined conditions or hard-to-access areas

کارشناسان توان گستر کاوه پارس آماده مشاوره و راهنمایی

جهت انتخاب محصول مناسب برای پروژه شما هستند

۰۹۱۲۲۵۶۵۷۴۳ – ۰۹۳۵۲۵۶۵۷۴۳

Table of contents

Important document information	3	Process	20
Symbols used	3	Process temperature range	20
Function and system design	4	Process pressure range	20
Measuring principle	4	Density	20
Measuring system	4	State of aggregation	20
Input	5	Viscosity	20
Measured variable	5	Solids contents	20
Measuring range	5	Lateral loading capacity	20
Output	5	Mechanical construction	21
Switch output	5	Design	21
Operating modes	5	Plug	22
Power supply	5	Tuning fork	22
Supply voltage	5	Sensor type	23
Power consumption	5	Weight	26
Current consumption	5	Materials	26
Residual ripple	5	Surface roughness	27
Residual voltage	5	Operability	28
Electrical connection	6	LED display	28
Cable entry	13	Function test with test magnet	29
Cable specification	13	Certificates and approvals	30
Overvoltage protection	13	CE mark	30
Performance characteristics	14	EAC conformity	30
Reference operating conditions	14	RCM-Tick marking	30
Switch point (with orientation: vertical from above)	14	Approval	30
Hysteresis	14	Overfill protection	30
Non-repeatability	14	Marine approvals	30
Influence of ambient temperature	14	CRN approval	30
Influence of medium temperature	14	Inspection certificates	30
Influence of medium pressure	14	Manufacturer declaration	30
Switching delay	14	Pressure Equipment Directive	30
Switch-on delay	14	Other standards and guidelines	30
Measuring frequency	14	Ordering information	31
Measured error	14	Ordering information	31
Mounting	15	Services (optional)	31
Orientation	15	Accessories	31
Installation instructions	15	Weld-in adapter	31
Length of connecting cable	17	Plug-in jack, cable	31
Environment	18	Additional accessories	32
Ambient temperature range	18	Supplementary documentation	34
Storage temperature	18	Operating Instructions Liquiphant FTL31	34
Climate class	18	Additional documentation	34
Altitude	18	Certificates	34
Degree of protection	19		
Shock resistance	19		
Vibration resistance	19		
Electromagnetic compatibility	19		
Reverse polarity protection	19		
Short-circuit protection	19		

Important document information

Symbols used

Symbols for certain types of information and graphics

-  **Permitted**
Procedures, processes or actions that are permitted
-  **Forbidden**
Procedures, processes or actions that are forbidden
-  **Tip**
Indicates additional information
-  **Reference to documentation**
-  **Reference to graphic**
-  **Notice or individual step to be observed**
-  **Series of steps**
-  **Result of a step**
-  **Item numbers**
-  **Views**


Function and system design

Measuring principle

A piezoelectric drive causes the tuning fork of the device to vibrate at its resonance frequency. When the tuning fork is immersed in a liquid, its intrinsic frequency changes due to the change in density of the surrounding medium. The electronics system in the point level switch monitors the resonance frequency and indicates whether the tuning fork is vibrating in air or is covered by liquid.

Measuring system

The measuring system consists of a point level switch, e.g. for connection to programmable logic controllers (PLC).



A0036961

1 Installation examples

- 1 Overfill protection or upper level detection (maximum safety)
- 2 Dry running protection for pump (minimum safety)
- 3 Lower level detection (minimum safety)

در این قسمت مشخصات فنی محصول آمده. برای مشاوره متناسب با نیاز پروژه تماس بگیرید: ۰۹۱۲۲۵۶۵۷۴۳

Input

Measured variable	Density
Measuring range	> 0.7 g/cm ³ (optionally available: > 0.5 g/cm ³)

Output

Switch output	Switching behavior: On/Off Function 3-wire DC-PNP: Positive voltage signal at the switch output of the electronics (PNP), switching capacity 200 mA 2-wire AC/DC: Load switching in the power supply line, switching capacity 250 mA
Operating modes	The device has two operating modes: maximum safety (MAX) and minimum safety (MIN). By choosing the corresponding operating mode, the user ensures that the device also switches in a safety-oriented manner even in an alarm condition, e.g. if the power supply line is disconnected. ■ Maximum safety (MAX) The device keeps the electronic switch closed as long as the liquid level is below the fork. Sample application: overfill prevention ■ Minimum safety (MIN) The device keeps the electronic switch closed as long as the fork is immersed in liquid. Sample application: Dry running protection for pumps The electronic switch opens if the limit is reached, if a fault occurs or the power fails (quiescent current principle).

Power supply

Supply voltage	DC-PNP 10 to 30 V DC, 3-wire AC/DC 20 to 253 VAC/DC, 2-wire
Power consumption	DC-PNP < 975 mW AC/DC < 850 mW
Current consumption	DC-PNP < 15 mA AC/DC < 3.8 mA
Residual ripple	DC-PNP 5 V_{ss} 0 to 400 Hz AC/DC —
Residual voltage	DC-PNP U < 3 V (for switched through transistor) AC/DC —

کارشناسان با تجربه ما با مشاوره تخصصی، متناسب با نیاز پروژه شما محصولات می‌کنند: ۰۹۱۲۲۵۶۵۷۴۳

Electrical connection

Two electronic versions and three different connections are available for the device.

- Electronic version 3-wire DC-PNP with connection; M12 plug, valve plug or cable
- Electronic version 2-wire AC/DC with connection; valve plug or cable

A fine-wire fuse is necessary for operation: 500 mA slow-blow.

Electronic version 3-wire DC-PNP

3-wire DC-PNP is preferably used in conjunction with programmable logic controllers (PLC), DI modules as per EN 61131-2. Positive signal at the switch output of the electronics (PNP).


Voltage source: non-hazardous contact voltage or Class 2 circuit (North America).

Connection with M12 plug

Depending on the analysis of the switch outputs, the device works in the MAX (maximum safety) or MIN (minimum safety) mode.



A cable is optionally available



A0022901

2 M12 plug

Maximum safety		
Terminal assignment	MAX output	Yellow LED (ye)
Wire colors for M12 plug: ▪ 1 = BN (brown) ▪ 2 = WT (white) ▪ 3 = BU (blue) ▪ 4 = BK (black)		
Symbols K	Description Yellow LED (ye) lit Yellow LED (ye) not lit External load	


Minimum safety		
Terminal assignment	MIN output	Yellow LED (ye)

Minimum safety		
Terminal assignment	MIN output	Yellow LED (ye)
Wire colors for M12 plug: 1 = BN (brown) 2 = WT (white) 3 = BU (blue) 4 = BK (black)		
Symbols	Description	
	Yellow LED (ye) lit	
	Yellow LED (ye) not lit	
K	External load	

Function monitoring with M12 plug


Using a two-channel analysis, function monitoring of the sensor can be implemented in addition to level monitoring, e.g. per relay switch, PLC, AS-i Bus I/O module.

When both outputs are connected, the MIN and MAX outputs assume opposite states (XOR) when the device is operating fault-free. In the event of an alarm condition or a line break, both outputs are de-energized.

Connection for function monitoring using XOR operation			Yellow LED (ye)	LED red (rd)
	Sensor covered	Max output  1/2		
		Min output  1/4		
	Sensor not covered	Max output  1/2		
		Min output  1/4		
	Fault	 1/2 1/4		
Wire colors for M12 plug: 1 = BN (brown) 2 = WT (white) 3 = BU (blue) 4 = BK (black)				
Symbols	Description			
	LED lit			
	LED not lit			
	Fault or warning			
K1/K2	External load			

Connection with valve plug

Depending on the assignment of the connector or the wiring of the cable, the device works in either the MAX or MIN operating mode.



A0022900


3 Valve plug

3-wire DC-PNP		
Terminal assignment	MAX operating mode	Yellow LED (ye)
	3 ← 2	
	3 ↗ 2	
Symbols	Description	
	Yellow LED (ye) lit	
	Yellow LED (ye) not lit	
K	External load	

3-wire DC-PNP		
Terminal assignment	MIN operating mode	Yellow LED (ye)
	2 ↘ 3	
	2 ← 3	
Symbols	Description	
	Yellow LED (ye) lit	
	Yellow LED (ye) not lit	
K	External load	


Connection with cable


Depending on the assignment of the connector or the wiring of the cable, the device works in either the MAX or MIN operating mode.



A0022902

4 Cable (cannot be disassembled)

3-wire DC-PNP		
Terminal assignment	MAX operating mode	Yellow LED (ye)
		
		
Wire colors: 1 = BK (black) 2 = GR (gray) 3 = BN (brown) Ground = GNYE (green-yellow)		
Symbols	Description	
	Yellow LED (ye) lit	
	Yellow LED (ye) not lit	
K	External load	


3-wire DC-PNP		
Terminal assignment	MIN operating mode	Yellow LED (ye)
		
		
Wire colors: 1 = BK (black) 2 = GR (gray) 3 = BN (brown) Ground = GNYE (green-yellow)		
Symbols	Description	
	Yellow LED (ye) lit	
	Yellow LED (ye) not lit	
K	External load	

Electronic version 2-wire AC/DC

The load is switched via an electronic switch directly in the power supply circuit. Always connect in series with a load!

Not suitable for connection to low-voltage PLC inputs!

Selection tool for relays



A0023486

 5 Minimum rated power of the load

P/S Rated power in [W] / [VA]

U Operating voltage in [V]

P1: AC mode

Relay operating voltage: Relay rated power

- 24 V: 1.3 to 6 VA
- 110 V: 1.5 to 27.5 VA
- 230 V: 2.5 to 57.5 VA

P2: DC mode


Relay operating voltage: Relay rated power

- 24 V: 0.7 to 6 W
- 48 V: 0.9 to 12 W
- 60 V: 1.5 to 15 W

 Relays with a lower rated power can be operated by means of an RC module connected in parallel (optional).


Connection with valve plug


Depending on the assignment of the connector or the wiring of the cable, the device works in either the MAX or MIN operating mode.



A0022900

 6 Valve plug


2-wire AC/DC		
Terminal assignment	MAX operating mode	Yellow LED (ye)
 A0021219	 A0045072	
	 A0045074	
Symbols   K	Description Yellow LED (ye) lit Yellow LED (ye) not lit External load	

2-wire AC/DC		
Terminal assignment	MIN operating mode	Yellow LED (ye)
 A0021220	 A0045070	
	 A0045069	
Symbols   K	Description Yellow LED (ye) lit Yellow LED (ye) not lit External load	

Connection with cable


Depending on the assignment of the connector or the wiring of the cable, the device works in either the MAX or MIN operating mode.


When the cable is wired, one wire of the cable does not have any function in each of the operating modes (brown in the case of MIN, and gray in the case of MAX). The cable with no function must be secured against inadvertent contact.




A0022902

 7 Cable (cannot be disassembled)

2-wire AC/DC		
Terminal assignment	MAX operating mode	Yellow LED (ye)
		
		
Wire colors: 1 = BK (black) 2 = GR (gray) 3 = BN (brown) Ground = GNYE (green-yellow)		
Symbols	Description	
	Yellow LED (ye) lit	
	Yellow LED (ye) not lit	
K	External load	

2-wire AC/DC		
Terminal assignment	MIN operating mode	Yellow LED (ye)
 A0022225	 A0045070	
	 A0045069	
Wire colors: 1 = BK (black) 2 = GR (gray) 3 = BN (brown) Ground = GNYE (green-yellow)		
Symbols	Description	
	Yellow LED (ye) lit	
	Yellow LED (ye) not lit	
K	External load	

Cable entry



A0020928

- A Valve plug (M16x1.5; NPT 1/2"; QUICKON)
 B M12 plug
 C Cable 5 m (16 ft); secured in place on delivery and cannot be disassembled

Cable specification

- Valve plug
 - Cable cross-section: max. 1.5 mm² (AWG 16)
 - Ø 3.5 to 8 mm (0.14 to 0.26 in)
- M12 plug: IEC 60947-5-2
- Cable (3LPE)
 - Cable cross-section: 0.75 mm² (AWG 20)
 - Ø 6 to 8 mm (0.24 to 0.31 in)
 - Material: PUR

Overvoltage protection

Overvoltage category II


Performance characteristics

Reference operating conditions	Ambient temperature:	+25 °C (+77 °F)
	Process pressure:	1 bar (14.5 psi)
	Fluid:	Water (density: approx. 1 g/cm ³ , viscosity 1 mm ² /s)
	Medium temperature:	25 °C (77 °F)
	Density setting:	> 0.7 g/cm ³
	Switching time delay:	Standard (0.5 s, 1 s)
Switch point (with orientation: vertical from above)	13 mm (0.51 in) ± 1 mm	
Hysteresis	Max. 3 mm (0.12 in)	
Non-repeatability	±1 mm (0.04 in) in accordance with DIN 61298-2	
Influence of ambient temperature	Negligible	
Influence of medium temperature	-25 µm (984 µin)/°C	
Influence of medium pressure	-20 µm (787 µin)/bar	
Switching delay	■ 0.5 s when tuning fork is covered ■ 1.0 s when tuning fork is uncovered ■ Optionally available: 0.2 s; 1.5 s or 5 s (when the tuning fork is covered and uncovered)	
Switch-on delay	Max. 3 s	
Measuring frequency	Approx. 1 100 Hz in air	
Measured error	In event of device change: ±2 mm (0.08 in) as per DIN 61298-2	

Mounting

Orientation

The point level switch can be installed in any position in a vessel, pipe or tank. Foam formation does not affect the function.



A0036961


8 Installation examples

- 1 Overfill protection or upper level detection (maximum safety)
- 2 Dry running protection for pump (minimum safety)
- 3 Lower level detection (minimum safety)

Installation instructions

Switch point

The switch point (A) on the sensor depends on the orientation of the point level switch (water +25 °C (+77 °F), 1 bar (14.5 psi)).




A0020734

9 Orientation: vertical from above, vertical from below, horizontal; dimensions in mm (in)

Short tube version

The use of the short tube ensures that the switch point is at the same level as in the previous Liquiphant FTL260 model when an identical thread is selected. In this way, the device can be replaced quickly and easily. (Applies for process connections G 1" weld-in adapter for flush mount installation, MNPT 1" and R 1")



A0022122

Dimensions mm (in)


A Liquiphant FTL31 with short tube

B Liquiphant FTL260

C Switch point

Installation in pipes

During installation, pay attention to the position of the fork in order to minimize turbulence in the pipe.




A0021357

Dimensions mm (in)

Installation in vessels

If installed horizontally, pay attention to the position of the tuning fork to ensure that the liquid can drip off.

The electrical connection, e.g. M12 plug, should be pointing down with the cable. This can prevent moisture from penetrating.




A0021034

10 Position of the fork in the case of horizontal installation in a vessel

Distance from wall

Ensure that there is sufficient distance between the expected buildup on the tank wall and the fork. Recommended distance from wall ≥ 10 mm (0.39 in).




A0022272

Length of connecting cable

- Up to 1000 m (3281 ft)
- Max. 25 Ω /wire, total capacitance < 100 nF

Environment

Ambient temperature range -40 to +70 °C (-40 to +158 °F)



A0022002


11 Derating curve: 100 °C (212 °F)

1 I_{max} : 200 mA (DC-PNP), 250 mA (AC/DC)

2 I_{max} : 150 mA (DC-PNP), 150 mA (AC/DC)

T_a Ambient temperature range

T_p Process temperature



A0020869

12 Derating curve: 150 °C (302 °F)

1 I_{max} : 200 mA (DC-PNP), 250 mA (AC/DC)

2 I_{max} : 150 mA (DC-PNP), 150 mA (AC/DC)

T_a Ambient temperature range

T_p Process temperature

Storage temperature -40 to +85 °C (-40 to +185 °F)

Climate class DIN EN 60068-2-38/IEC 68-2-38: test Z/AD

Altitude Up to 2 000 m (6 600 ft) above sea level

Degree of protection	■ IP65/67 NEMA Type 4X Enclosure (M12 plug) ■ IP66/68/69 NEMA Type 4X/6P Enclosure (M12 plug for metal housing cover) ■ IP65 NEMA Type 4X Enclosure (valve plug) ■ IP66/68 NEMA Type 4X/6P Enclosure (cable)
Shock resistance	$a = 300 \text{ m/s}^2 = 30 \text{ g}$, 3 axes x 2 directions x 3 shocks x 18 ms, as per test Ea, prEN 60068-2-27:2007
Vibration resistance	$a(\text{RMS}) = 50 \text{ m/s}^2$, $\text{ASD} = 1.25 (\text{m/s}^2)^2/\text{Hz}$, $f = 5 \text{ to } 2\,000 \text{ Hz}$, $t = 3 \times 2 \text{ h}$, as per test Fh, EN 60068-2-64:2008
Electromagnetic compatibility	Electromagnetic compatibility in accordance with all relevant requirements of the EN 61326 series and NAMUR recommendation EMC (NE21). For details, refer to the EC Declaration of Conformity. The EC Declaration of Conformity is available in the Download Area of the Endress+Hauser website: www.endress.com → Downloads.
Reverse polarity protection	2-wire AC/DC ■ AC mode: the device has reverse polarity protection. ■ DC mode: in the event of reverse polarity the maximum safety mode is always detected. Check the wiring and perform a function check before commissioning. The device is not damaged in the event of reverse polarity. 3-wire DC-PNP Integrated. In the event of reverse polarity, the device is deactivated automatically.
Short-circuit protection	2-wire AC/DC During switching the sensor checks whether a load, e.g. relay or contactor, is present (load check). If an error occurs, the sensor is not damaged. Smart monitoring: normal operation is resumed once the error is fixed. 3-wire DC-PNP Overload protection/short-circuit protection at $I > 200 \text{ mA}$; the sensor is not destroyed. Intelligent monitoring: Testing for overload at intervals of approx. 1.5 s; normal operation resumes once the overload/short-circuit has been rectified.

Process


Process temperature range	-40 to +100 °C (-40 to +212 °F) -40 to +150 °C (-40 to +302 °F)
Process pressure range	Max. -1 to +40 bar (-14.5 to +580 psi)
Density	> 0.7 g/cm ³ (optionally available: > 0.5 g/cm ³)
State of aggregation	Liquid
Viscosity	1 to 10 000 mPa·s, dynamic viscosity
Solids contents	ø < 5 mm (0.2 in)
Lateral loading capacity	Lateral loading capacity of the tuning fork: maximum 200 N

Mechanical construction

Design

The point level switch is available in different versions, which can be assembled in accordance with user specifications.

The versions can be selected via the product structure in the Product Configurator, see the "Ordering information" section . Examples in the graphic below:



Versions	Examples			
	A	B	C	D
Electrical connection	Valve plug	Cable (cannot be disassembled)	M12 plug for housing cover IP66/68/69	M12 plug for housing cover IP65/67
Housing (sensor design) for process temperatures up to:	100 °C (212 °F) or 150 °C (302 °F)	100 °C (212 °F) or 150 °C (302 °F)	100 °C (212 °F) or 150 °C (302 °F)	100 °C (212 °F) or 150 °C (302 °F)
Sensor type	Compact version	Short tube version	Compact version	Short tube version






-  For detailed information on the process connections, see the "Mechanical construction" -> "Sensor type" section
-  For information on the short tube version, see the "Mounting" -> "Installation instructions" section

Plug

Dimensions

Dimensions mm (in)


The following graphics illustrate the plugs together with the suitable housing covers on the housing of the point level switch.



Electrical connection with housing cover		Designation
A  A0021859	B  A0044300	A: Valve plug M16, NPT ½" for housing cover: PPSU plastic (IP65) B: Valve plug QUICKON for housing cover: PPSU plastic (IP65)
A  A0021858	B  A0021857	A: M12 plug for housing cover: 316L (IP66/68/69) B: M12 plug for housing cover: PPSU plastic (IP65/67)
 A0021692		Captive cable with housing cover: PPSU plastic (IP66/68)



Tuning fork



Dimensions



Dimensions mm (in)





Sensor type	Dimensions	
	Dimensions mm (in)	
	The total dimensions of the device can vary depending on the plug selected.	
	Information on the following tables	
	■ Meaning of symbols: * Dimension for process temperature max. 100 °C (212 °F) ** Dimension for process temperature max. 150 °C (302 °F) ■ If several versions have the same dimensions, one example of the compact version and one example of the short tube version is given. ■ The versions in the second column refer to the process connections in the product structure.	
	 For information on weld-in adapters, see the "Weld-in adapters, process adapters and flanges" documentation, TI00426F. →  34. Available in the Download Area of the Endress+Hauser website www.endress.com/downloads.	
Dimensions	Version	Description
 Technical drawing of the compact version sensor. Dimensions: 136.6 (5.38)** (total length), 112 (4.41)* (length to seal), 63.9 (2.52) (length to process connection), 38 (1.5) (process connection length), 16 (0.63) (flange thickness), 32 (flange width), 31.5 (1.24) (tube diameter). 13 Compact version, example G ½"	WBJ WCJ	Thread ISO 228 G ½" Thread ISO 228 G ¾" ■ Material: 316L ■ Scope of delivery: flat seal (FA) ■ Pressure and temperature (maximum): +40 bar (+580 psi) at +150 °C (+302 °F)
 Technical drawing of the short tube version sensor. Dimensions: 176 (6.93)** (total length), 151.4 (5.96)* (length to seal), 103.3 (4.07) (length to process connection), 38 (1.5) (process connection length), 16 (0.63) (flange thickness), 32 (flange width), 31.5 (1.24) (tube diameter), 17.1 (0.7) (short tube diameter). 14 Short tube version, example G ½"	W5J	Thread ISO 228 G ¾" for flush mount installation in weld-in adapter ■ Material: 316L ■ Scope of delivery: flat seal (FA) Accessory: weld-in adapter ■ Scope of delivery: seal (VMQ) ■ Pressure and temperature (maximum): +25 bar (+352 psi) at +150 °C (+302 °F) +40 bar (+580 psi) at +100 °C (+212 °F) The dimensions apply for G ½"; G ¾" and G ¾" for flush mount installation.

Dimensions	Version	Description
 15 Compact version	WDJ	Thread ISO 228 G 1" - Material: 316L - Scope of delivery: flat seal (FA) - Pressure and temperature (maximum): +40 bar (+580 psi) at +150 °C (+302 °F)
 16 Short tube version		

Dimensions	Version	Description
 17 Compact version	WSJ	Thread ISO 228 G 1" for flush mount installation in weld-in adapter - Material: 316L - Scope of delivery: flat seal (FA) Accessory: weld-in adapter - Scope of delivery: seal (VMQ) - Pressure and temperature (maximum): +25 bar (+362 psi) at +150 °C (+302 °F) +40 bar (+580 psi) at +100 °C (+212 °F)
 18 Short tube version		

Dimensions	Version	Description
 136.6 (5.38)** 112 (4.41)* 63.9 (2.52) 47.9 (1.89) 38 (1.5) 31.5 (1.24) 32 A0021788 19 Compact version, example MNPT 3/4"	VAJ VBJ XBJ XCJ	Thread ASME MNPT 1/2" Thread ASME MNPT 3/4" Thread EN10226 R 1/2" Thread EN10226 R 3/4" Pressure and temperature (maximum): +40 bar (+580 psi) at +150 °C (+302 °F) The dimensions apply for MNPT 1/2", MNPT 3/4", R 1/2" and R 3/4".
 176 (6.93)** 151.4 (5.96)* 103.3 (4.07) 87.3 (3.44) 38 (1.5) 31.5 (1.24) 32 17.1 (0.7) A0021895 20 Short tube version, example MNPT 3/4"		

Dimensions	Version	Description
 21 Compact version, example MNPT 1"	VCJ XDJ	Thread ASME MNPT 1" Thread EN10226 R 1" Pressure and temperature (maximum): +40 bar (+580 psi) at +150 °C (+302 °F) The dimensions apply for MNPT 1" and R 1".
 22 Short tube version, example MNPT 1"		

-  Pay attention to the temperature and pressure specifications for seals used at the customer site.
-  Endress+Hauser supplies DIN/EN process connections with threaded connection in stainless steel in accordance with AISI 316L (DIN/EN material number 1.4404 or 1.4435). In terms of their stability-temperature property, the materials 1.4404 and 1.4435 are grouped in EN 1092-1 table 18 under 13EO. The chemical composition of the two materials can be identical.

Weight	Sensor type	Weight
	Compact version with process adapter G ½" and valve plug for process temperature up to 100 °C (212 °F)	Approx. 140 g (4.938 oz)
	Short tube version with process adapter G ½" and valve plug for process temperature up to 150 °C (302 °F)	Approx. 169 g (5.961 oz)

Materials Material specifications in accordance with AISI and DIN EN.

Materials in contact with process

Component part	Material
Tuning fork	316L
Process adapter	316L (1.4404/1.4435)
Short tube	316L (1.4404/1.4435)
Seal for weld-in adapter with G ¾", G 1"	VMQ
Flat seal	FA (composite material based on aramid fibers combined with NBR)

Materials not in contact with process

Component part	Material
Housing cover with M12 plug (IP66/68/69)	316L
Housing cover with M12 plug (IP65/67)	PPSU
Housing cover with valve plug (IP65)	
Housing cover with cable (IP66/68)	
Cable gland	PVDF
Design ring	PBT/PC
Housing	316L (1.4404/1.4435)

Surface roughness

Metallic surface in contact with process:


Ra ≤3.2 µm (126 µin)



The surface is not defined in the area of the welding seam.

Operability

LED display




A0016856

- A M12 plug, (cable without graphic)
B Valve plug
1 Green LED (gn)
2 Yellow LED (ye)
3 LED red

Function	Description
Green LED (gn) Lit	Device is operational
Yellow LED (ye) Lit	M12 plug Indicates the sensor state: tuning fork is covered by liquid Valve plug / cable Indicates the switching state: - MAX operating mode (overflow protection): sensor is not covered by liquid - MIN operating mode (dry running protection): the sensor is covered by liquid
LED red (rd) Flashing	Warning/maintenance required: error can be rectified, e.g. incorrect wiring; protective function if test magnet is held against the sensor for longer than 30 s
LED red (rd) Lit	Fault/device failure: error cannot be rectified, e.g. electronic error

i On the metal housing cover (IP69), there is no external signaling via LEDs.



A0020871

Description of M12 plug with LED display (optional)

- LED gn: is lit when the supply voltage is applied
- LED ye 1: is lit when the sensor is covered
- LED ye 2: is lit when the sensor is **not** covered

i The connecting cable with an M12 plug and LED display can be optionally ordered as an accessory. See the "Accessories" section

Function test with test magnet


Carry out a function test while the device is in operation.

- Hold the test magnet for at least 2 s against the marking on the housing.
 - ↳ This inverts the current switch status, and the yellow LED changes state. When the magnet is removed, the switch status valid at that time is adopted.

If the test magnet is held against the marking for longer than 30 s, the red LED will flash: the device returns automatically to the current switch status.



The test magnet is not included in the scope of delivery. It can optionally be ordered as an accessory. See the "Accessories" -> "Additional accessories" section



A0020960

23 Position for test magnet on housing

Certificates and approvals



The following documents are also available in the Download Area of the Endress+Hauser website: www.endress.com → Downloads.

CE mark	The measuring system complies with the statutory requirements of the applicable EC Directives. These are listed in the corresponding EC Declaration of Conformity together with the standards applied. Endress+Hauser confirms successful testing of the device by affixing to it the CE mark.
EAC conformity	The measuring system meets the legal requirements of the applicable EAC guidelines. These are listed in the corresponding EAC Declaration of Conformity together with the standards applied. Endress+Hauser confirms successful testing of the device by affixing to it the EAC mark.
RCM-Tick marking	The supplied product or measuring system meets the ACMA (Australian Communications and Media Authority) requirements for network integrity, interoperability, performance characteristics as well as health and safety regulations. Here, especially the regulatory arrangements for electromagnetic compatibility are met. The products are labelled with the RCM- Tick marking on the name plate.  AO029561
Approval	CSA C/US General Purpose
Overfill protection	Prior to mounting the device, pay attention to the WHG approval documents. The documents are available on the Endress+Hauser website: www.endress.com → Downloads. WHG - Overfill detection system: Z-65.11-531 - Leak detection system: Z-65.40-532
Marine approvals	- GL (Germanischer Lloyd)/ DNV (Det Norske Veritas) - ABS (American Bureau of Shipping) - LR (Lloyd's Register) - BV (Bureau Veritas)
CRN approval	Versions with a CRN approval (Canadian Registration Number) are listed in the corresponding registration documents. CRN-approved devices are labeled with registration number 0F16950.5C on the nameplate. For further details on the maximum pressure values, see the Download Area of the Endress+Hauser website.
Inspection certificates	The following documents can be ordered with the device (optional): - Acceptance test certificate as per EN 10204-3.1 - Final inspection report
Manufacturer declaration	The following manufacturer declarations can be ordered (optional): - FDA conformity - TSE-free, materials free from animal origin - ROHS-compliant in accordance with Endress+Hauser regulation
Pressure Equipment Directive	The device does not fall within the scope of Pressure Equipment Directive 97/23/EC as it does not have a pressurized housing as defined in Article 1, Section 2.1.4 of the directive.
Other standards and guidelines	The applicable European guidelines and standards can be found in the relevant EU Declarations of Conformity.

Ordering information

Ordering information

Detailed ordering information is available from your nearest sales organization www.addresses.endress.com or in the Product Configurator under www.endress.com.



Product Configurator - the tool for individual product configuration

- Up-to-the-minute configuration data
- Depending on the device: Direct input of measuring point-specific information such as measuring range or operating language
- Automatic verification of exclusion criteria
- Automatic creation of the order code and its breakdown in PDF or Excel output format
- Ability to order directly in the Endress+Hauser Online Shop

Services (optional)

In addition, the following services can be selected via the product structure in the Product Configurator:

- Cleaned of oil+grease
- PWIS-free (PWIS = paint-wetting impairment substances)
- Density setting > 0.5 g/cm³
- Switching delay setting


Accessories

Weld-in adapter

Various weld-in adapters are available for installation in vessels or pipes.



The adapters are optionally available with inspection certificate 3.1 EN10204.

View (example)	Description
 <i>1 Leakage hole</i>	G ¾" ø29 pipe installation ø50 vessel installation FDA-listed materials as per 21 CFR Part 175-178
	G 1" ø53 pipe installation ø60 vessel installation

If installed horizontally and weld-in adapters with a leakage hole are used, ensure that the leakage hole is pointing down. This allows leaks to be detected as quickly as possible.



For detailed information, see "Technical Information" TI00426F (Weld-in adapters, process adapters and flanges)

Available in the Download Area of the Endress+Hauser website (www.endress.com/downloads).

Plug-in jack, cable



The plug-in jacks listed are suitable for use in the temperature range -25 to +70 °C (-13 to +158 °F).



Wire colors of M12 plug-in jacks:

1 = BN (brown), 2 = WT (white), 3 = BU (blue), 4 = BK (black)

Engineering unit mm (in)

Plug-in jack M12 IP69 with LED	Description	Order number
A0020871	- Angled - Terminated at one end 5 m (16 ft) PVC cable (orange) - Slotted nut 316L - Body: PVC (transparent)	52018763


Plug-in jack M12 IP69	Description	Order number
A0023713	- Terminated at one end - Angled 5 m (16 ft) PVC cable (orange) - Slotted nut 316L - Body: PVC (orange)	52024216

Plug-in jack M12 IP67	Description	Order number
A0022292	- Angled 5 m (16 ft) PVC cable (gray) - Slotted nut Cu Sn/Ni - Body: PUR (black)	52010285

Plug-in jack M12 IP67	Description	Order number
A0022293	- Self-terminated connection to M12 plug - Slotted nut Cu Sn/Ni - Body: PBT	52006263

Additional accessories

Socket wrench for mounting	Description	Order number
A0022273	- Hexagonal - Size across flats AF32	52010156

Test magnet	Description	Order number
 A0021732	Information in the "Operation" section	71267011

Supplementary documentation

-  For an overview of the scope of the associated Technical Documentation, refer to the following:
- *W@M Device Viewer* (www.endress.com/deviceviewer): Enter the serial number from nameplate
 - *Endress+Hauser Operations App*: Enter the serial number from the nameplate or scan the 2D matrix code (QR code) on the nameplate

Operating Instructions Liquiphant FTL31	 BA01285F
Additional documentation	Weld-in adapters, process adapters and flanges (overview)  TI00426F Weld-in adapter (installation instructions)  SD01622Z Valve plug (installation instructions)  SD00356F
Certificates	Overfill protection  ZE01010F Leak  ZE01011F



www.addresses.endress.com
